

SUBCHAPTER 6 COMMERCIAL DISTRICTS

295-601. Purposes. For the purpose of regulating the use of land in the city of Milwaukee and to provide for the orderly growth and development of the city, the following commercial zoning districts are established:

1. **NEIGHBORHOOD SHOPPING DISTRICTS (NS1-NS2).** These districts provide for residential uses as well as commercial uses that serve the neighborhood. Such commercial uses are necessary to satisfy basic shopping and service needs that occur frequently and must, therefore, be located close to residential areas. The character of these districts is intended to be compatible with that of surrounding residential neighborhoods. Buildings in these districts are typically smaller in scale than those found in local business districts. The NS1 district is characterized by a more suburban development pattern, with larger lots and deeper setbacks, while the development pattern in the NS2 district tends to be more urban, with smaller lots and smaller setbacks.

2. **LOCAL BUSINESS DISTRICTS (LB1-LB2).** These districts provide a wide range of goods and services to a large consumer population coming from an extensive area. Within these districts, motor-vehicle-related activities are of major significance. Good access by motor vehicle or public transit is important to local business districts, which are often located adjacent to intersections of major thoroughfares and in close proximity to bus transfer locations. The LB1 district is characterized by a more suburban development pattern, with larger lots and deeper setbacks, while the development pattern in the LB2 district tends to be more urban, with smaller lots and smaller setbacks.

3. **REGIONAL BUSINESS DISTRICTS (RB1-RB2).** These districts provide areas where regional or city-wide shopping, employment or high-density residential uses may occur. These districts allow large-scale and tall buildings. They also have a high intensity of land use and may contain nodes of development that can be effectively served by public transportation. The RB1 district is characterized by a more suburban development pattern, with larger lots and deeper setbacks, while the development pattern in the RB2 district tends to be more urban, with smaller lots and smaller setbacks.

4. **COMMERCIAL SERVICE (CS).** This district is intended to provide areas where businesses and personal service establishments can be accommodated, but where extensive retail activities are not warranted by city plans.

295-603. Uses. 1. **USE TABLE.** Table 295-603-1 indicates the use classifications for various land uses in the commercial districts. The uses in this table are defined in s. 295-201. The following are the use classifications indicated in Table 295-603-1:

a. "Y" indicates a permitted use. This use is permitted as a matter of right subject to all performance standards.

b. "L" indicates a limited use. This use is permitted only when the use meets the standards of sub. 2. If the use cannot meet these standards, it shall be permitted only upon board approval of a special use permit pursuant to s. 295-311-2, unless otherwise prohibited by sub. 2.

c. "S" indicates a special use. This use is permitted only if the board approves a special use permit pursuant to s. 295-311-2.

d. "N" indicates a prohibited use.

Table 295-603-1 COMMERCIAL DISTRICTS USE TABLE								
Y=Permitted Use S=Special Use	L=Limited Use N=Prohibited Use		Zoning Districts					
Uses	NS1	NS2	LB1	LB2	RB1	RB2	CS	
RESIDENTIAL USES								
Single-family dwelling	Y	Y	Y	Y	Y	Y	Y	
Two-family dwelling	Y	Y	Y	Y	Y	Y	Y	
Multi-family dwelling	Y	Y	Y	Y	Y	Y	Y	
Attached single-family dwelling	Y	Y	Y	Y	Y	Y	Y	
Live-work unit	Y	Y	Y	Y	Y	Y	Y	
Mobile home	N	N	N	N	N	N	N	
Watchman/service quarters	N	N	N	N	N	N	N	
Family day care home	L	L	L	L	L	L	L	
Group Residential								
Rooming house	S	S	S	S	S	S	S	
Convent, rectory or monastery	Y	Y	Y	Y	Y	Y	Y	
Dormitory	S	S	S	S	S	S	S	
Fraternity or sorority	S	S	S	S	S	S	S	
Adult family home	L	L	L	L	L	L	L	
Foster Homes								
Foster family home	Y	Y	Y	Y	Y	Y	Y	
Small foster home	L	L	L	L	L	L	L	
Group home or group foster home	L	L	L	L	L	L	L	
Shelter Care Facilities								
Family shelter care facility	Y	Y	Y	Y	Y	Y	Y	
Small group shelter care facility	L	L	L	L	L	L	L	
Large group shelter care facility	S	S	S	S	S	S	S	
Community living arrangement	L	L	L	L	L	L	L	
Transitional living facility	S	S	S	S	S	S	S	

Table 295-603-1 COMMERCIAL DISTRICTS USE TABLE							
Y=Permitted Use S=Special Use	L=Limited Use N=Prohibited Use		Zoning Districts				
USES	NS	NS	LB1	LB2	RB	RB2	C
EDUCATIONAL USES							
Day care center	L	L	L	L	L	L	L
School, elementary or secondary	S	S	S	S	S	S	S
College	Y	Y	Y	Y	Y	Y	Y
School, specialty or personal instruction	Y	Y	Y	Y	Y	Y	Y
COMMUNITY-SERVING USES							
Library	Y	Y	Y	Y	Y	Y	Y
Cultural institution	Y	Y	Y	Y	Y	Y	Y
Community center	S	S	S	S	S	S	S
Religious assembly	S	S	S	S	Y	Y	Y
Cemetery or other place of interment	N	N	N	N	N	N	N
Public safety facility	Y	Y	Y	Y	Y	Y	Y
Correctional facility	N	N	N	N	N	N	N
COMMERCIAL AND OFFICE USES							
General office	Y	Y	Y	Y	Y	Y	Y
Government office	Y	Y	Y	Y	Y	Y	Y
Bank or other financial institution	Y	Y	Y	Y	Y	Y	Y
Currency exchange, payday loan or title loan agency	S	S	S	S	S	S	S
Retail establishment, general	L	L	L	L	L	L	L
Garden supply or landscaping center	N	N	Y	Y	Y	Y	Y
Home improvement center	N	N	S	S	Y	Y	Y
Secondhand store	S	S	S	S	S	S	S
Outdoor merchandise sales	S	S	S	S	S	S	S
Artist studio	Y	Y	Y	Y	Y	Y	Y
Adult retail establishment	N	N	N	N	S	S	N
HEALTH CARE AND SOCIAL ASSISTANCE USES							
Medical office	Y	Y	Y	Y	Y	Y	Y
Health clinic	S	S	S	S	S	S	S
Hospital	N	N	S	S	S	S	S
Medical research laboratory	N	N	S	S	S	S	Y
Medical service facility	N	N	S	S	S	S	S
Social service facility	S	S	S	S	S	S	S
Emergency residential shelter	S	S	S	S	S	S	S
Nursing home	S	S	Y	Y	Y	Y	Y
GENERAL SERVICE USES							
Personal service	Y	Y	Y	Y	Y	Y	Y
Business service	Y	Y	Y	Y	Y	Y	Y
Building maintenance service	N	N	S	S	Y	Y	Y
Catering service	Y	Y	Y	Y	Y	Y	Y
Funeral home	Y	Y	Y	Y	Y	Y	Y
Laundromat	Y	Y	Y	Y	Y	Y	Y
Dry cleaning establishment	Y	Y	Y	Y	Y	Y	Y
Furniture and appliance rental and leasing	S	S	Y	Y	Y	Y	Y
Household maintenance and repair service	Y	Y	Y	Y	Y	Y	Y

295-603-1 Zoning

Table 295-603-1 COMMERCIAL DISTRICTS USE TABLE							
Y=Permitted Use S=Special Use USES	L=Limited Use N=Prohibited Use		Zoning Districts				
	NS	NS	LB1	LB2	RB	RB2	C
Tool/equipment rental facility	Y	Y	Y	Y	Y	Y	Y
<i>Animal Services</i>							
Animal hospital/clinic	L	L	L	L	L	L	L
Animal boarding facility	L	L	L	L	L	L	L
Animal grooming or training facility	L	L	L	L	L	L	L
MOTOR VEHICLE USES							
<i>Light Motor Vehicle</i>							
Sales facility	N	N	S	S	Y	Y	S
Rental facility	L	L	L	L	Y	Y	Y
Repair facility	N	N	S	S	S	S	S
Body shop	N	N	S	S	S	S	S
Outdoor storage	N	N	S	S	S	S	S
Limited wholesale facility	Y	Y	Y	Y	Y	Y	Y
<i>Heavy Motor Vehicle</i>							
Sales facility	N	N	S	S	S	S	S
Rental facility	N	N	S	S	S	S	S
Repair facility	N	N	N	N	S	S	N
Body shop	N	N	N	N	S	S	N
Outdoor storage	N	N	N	N	S	S	N
<i>General Motor Vehicle</i>							
Filling station	N	N	S	S	S	S	S
Car wash	N	N	L	L	L	L	L
Drive-through facility	L	L	L	L	L	L	L
<i>Parking</i>							
Parking lot, principal use	L	L	Y	L	Y	L	L
Parking lot, accessory use	Y	L	Y	L	Y	Y	Y
Parking structure, principal use	S	S	L	L	L	L	L
Parking structure, accessory use	Y	L	Y	L	Y	Y	Y
Heavy motor vehicle parking lot, principal use	N	N	S	S	S	S	S
Heavy motor vehicle parking lot, accessory use	S	S	S	S	S	S	S
ACCOMMODATION AND FOOD SERVICE USES							
Bed and breakfast	Y	Y	Y	Y	Y	Y	Y
Hotel, commercial	Y	Y	Y	Y	Y	Y	Y
Hotel, residential	Y	Y	Y	Y	Y	Y	Y
Tavern	L	L	Y	Y	Y	Y	Y
Assembly hall	S	S	S	S	S	S	S
Restaurant, sit-down	Y	Y	Y	Y	Y	Y	Y
Restaurant, fast-food/carry-out	L	L	L	L	L	L	L
ENTERTAINMENT AND RECREATION USES							
Park or playground	Y	Y	Y	Y	Y	Y	Y
Festival grounds	N	N	N	N	N	N	N
Recreation facility, indoor	S	S	Y	Y	Y	Y	Y
Recreation facility, outdoor	S	S	S	S	S	S	S
Health club	Y	Y	Y	Y	Y	Y	Y
Sports facility	N	N	S	S	S	S	S

Table 295-603-1 COMMERCIAL DISTRICTS USE TABLE							
Y=Permitted Use S=Special Use	L=Limited Use N=Prohibited Use	Zoning Districts					
USES	NS	NS	LB1	LB2	RB	RB2	C
Gaming facility	N	N	N	N	N	N	N
Theater	L	L	Y	Y	Y	Y	Y
Convention and exposition center	N	N	S	S	S	S	S
Marina	Y	Y	Y	Y	Y	Y	Y
Outdoor racing facility	N	N	N	N	N	N	N
Adult entertainment establishment	N	N	N	N	S	S	N
STORAGE, RECYCLING AND WHOLESALE TRADE USES							
Recycling collection facility	S	S	S	S	S	S	S
Mixed-waste processing facility	N	N	N	N	N	N	N
Material reclamation facility	N	N	N	N	N	N	N
Salvage operation, indoor	N	N	N	N	N	N	S
Salvage operation, outdoor	N	N	N	N	N	N	N
Wholesale and distribution facility, indoor	S	S	L	L	L	L	Y
Wholesale and distribution facility, outdoor	N	N	S	S	S	S	S
Storage Facilities							
Indoor	S	S	L	L	L	L	Y
Outdoor	N	N	S	S	S	S	S
Hazardous materials	N	N	N	N	N	N	N
TRANSPORTATION USES							
Ambulance service	N	N	S	S	Y	Y	S
Ground transportation service	N	N	S	S	S	S	L
Passenger terminal	N	N	Y	Y	Y	Y	Y
Helicopter landing facility	N	N	S	S	S	S	S
Airport	N	N	N	N	N	N	N
Ship terminal or docking facility	N	N	N	N	N	N	N
Truck freight terminal	N	N	N	N	N	N	N
Railroad switching, classification yard or freight terminal	N	N	N	N	N	N	N
INDUSTRIAL USES							
Manufacturing, light	N	N	L	L	L	L	L
Manufacturing, heavy	N	N	N	N	N	N	N
Manufacturing, intense	N	N	N	N	N	N	N
Research and development	N	N	S	S	S	S	S
Processing or recycling of mined materials	N	N	N	N	N	N	N
Contractor's shop	N	N	L	L	L	L	L
Contractor's yard	N	N	S	S	S	S	S
AGRICULTURAL USES							
Plant nursery or greenhouse	N	N	N	N	N	N	N
Raising of crops or livestock	N	N	N	N	N	N	N
UTILITY AND PUBLIC SERVICE USES							
Broadcasting or recording studio	N	N	Y	Y	Y	Y	Y
Transmission tower	L	L	L	L	L	L	L
Water treatment plant	S	S	Y	Y	Y	Y	Y
Sewage treatment plant	N	N	N	N	N	N	N
Power generation plant	N	N	N	N	N	N	N

Table 295-603-1 COMMERCIAL DISTRICTS USE TABLE							
USES	Y=Permitted Use S=Special Use		L=Limited Use N=Prohibited Use		Zoning Districts		
	NS	NS	LB1	LB2	RB	RB	C
Substation/distribution equipment, indoor	S	S	S	S	S	S	S
Substation/distribution equipment, outdoor	L	L	L	L	L	L	L
TEMPORARY USES							
Seasonal market	L	L	L	L	L	L	L
Temporary real estate sales office	L	L	L	L	L	L	L
Concrete/batch plant, temporary	L	L	L	L	L	L	L
Live entertainment special event	L	L	L	L	L	L	L

- 2. LIMITED USE STANDARDS.** a. Family Day Care Home. a-1. The operator of the family day care home shall reside in the dwelling unit in which the day care home is located, except in a 2-family dwelling, in which case the operator may reside in one dwelling unit and operate the family day care home in the other unit.
- a-2. There shall be no other family day care home in the building as of April 30, 2004.
- a-3. The family day care home shall not operate between the hours of 10 p.m. and 6 a.m.
- a-4. Signs shall not be permitted.
- a-5. Any family day care home that does not meet one or more of these standards shall be classified as a day care center.
- b. Adult Family Home or Small Group Shelter Care Facility.
- b-1. Adult Family Home. The use shall not be located within 2,500 feet of a community living arrangement, small foster home, group home or group foster home, or another adult family home.
- b-2. Small Group Shelter Care Facility. The use shall not be located within 2,500 feet of a community living arrangement, adult family home, small foster home, group home or group foster home, large group shelter care facility or another small group shelter care facility.
- c. Small Foster Home. The use shall not be located within 2,500 feet of a community living arrangement, group home or group foster home, or another small foster home.
- d. Group Home, Group Foster Home or Community Living Arrangement. d-1. The use shall not be located within 2,500 feet of a small foster home or another group home, group foster home or community living arrangement.
- d-2. Not more than 15 persons shall reside on the premises.
- d-3. The use has not been determined by the common council to be a nuisance under s. 62.23(7)(i), Wis. Stats.
- e. Day Care Center. e-1. The use is located in a building containing an elementary or secondary school, college, library or cultural institution as a principal use.
- e-2. The use shall not operate between the hours of 12 a.m. and 5 a.m.
- f. General Retail Establishment. The use shall not be operated between 12 a.m. and 5 a.m. if it is located within 150 feet of a residential district. This limitation shall not apply to a convenience store which is open between the hours of 12 a.m. and 5 a.m. and regulated by s. 84-7.
- g. Animal Hospital/Clinic, Animal Boarding Facility or Animal Grooming or Training Facility. No outdoor run or outdoor kennels shall be provided on the premises.
- h. Light Motor Vehicle Rental Facility. Not more than 15 vehicles available for rent may be kept on the premises.

- i. Car Wash. i-1. If any mechanical washing equipment is used:
 - i-1-a. The car wash shall not be located within 150 feet of a residential use.
 - i-1-b. Washing and cleaning shall be conducted on a line of operation within a building which is constructed so as to prevent any liquid or resultant spray or mist from crossing any property line of the premises.
 - i-1-c. One or more driving lanes shall be provided to allow for continuous movement of vehicles into the washing and cleaning operations. If access to the line of operation is limited to a single lane, the lane shall be used exclusively for the washing and cleaning operation.
 - i-1-d. Each driving lane shall be not less than 10 feet wide.
 - i-1-e. A queue lane of at least 200 feet in length shall be provided on the premises.
 - i-1-f. All wastewater shall be contained entirely on the premises.
- i-2. If no mechanical washing equipment is used:
 - i-2-a. The car wash shall not be located within 150 feet of a residential use.
 - i-2-b. Washing and cleaning shall be conducted within a building which is constructed so as to prevent any liquid or resultant spray or mist from crossing any property line of the premises.
 - i-2-c. One or more driving lanes shall be provided to allow for continuous movement of vehicles into the washing and cleaning operations.
 - i-2-d. Parking for at least 4 vehicles shall be provided on the premises.
 - i-2-e. All wastewater shall be contained entirely on the premises.
- j. Drive-through Facility. j-1. A queue lane of at least 200 feet shall be provided on the premises.
 - j-2. The facility shall not be operated between the hours of 10 p.m. and 7 a.m. This limitation shall not apply to an automatic teller machine or a drive-through facility associated with a convenience store, personal service, filling station, sit-down restaurant or fast food/carry-out restaurant which is open between the hours of 12 a.m. and 5 a.m. and regulated by s. 84-7.
 - j-3. The facility shall not be located within 150 feet of a residential use.
 - j-4. Any lights associated with the facility shall be controlled so as to prevent glare or spill light on residential properties, as prohibited by ch. 80.
 - j-5. If the facility is visible from a public street or a residential district, an opaque screen shall be provided along the visible portion of the drive-through queuing and operating lane.
- k. Parking Lot, Principal Use. k-1. The width of the paved parking area shall not exceed 60 feet as measured from side lot line to side lot line.
 - k-2. The parking lot shall not be immediately adjacent to another premises containing a parking lot as a principal use.
 - k-3. No alley shall be relied upon for vehicular circulation purposes.
 - k-4. The parking lot shall not be located on a corner lot.
- L. Parking Lot, Accessory Use. The parking lot shall not be located between the street façade of a principal building and a street lot line.
- m. Parking Structure, Principal Use or Accessory Use. At least 50% of the street frontage of the street-level area shall be occupied by one or more other uses listed as permitted in the district or otherwise approved by the board.
- n. Tavern. The structure to be occupied was constructed prior to October 1, 2002, was originally designed and intended to be occupied in whole or in part by a non-residential use and has been continuously occupied by such non-residential use.
- o. Fast-food/Carry-out Restaurant. The use shall be located in a building containing at least one other principal use listed as a permitted use in the zoning district in which it is located.
- p. Theater. The capacity of the building shall not exceed 49 persons.
- q. Indoor Wholesale and Distribution Facility or Indoor Storage Facility. q-1. The gross floor area of the building devoted to storage as a principal use shall not exceed 3,600 square feet.
 - q-2. Storage of hazardous materials, as described in s. 295-201-627, shall be prohibited.
- r. Ground Transportation Service. r-1. Not more than 15 vehicles shall be stored on the premises at any one time.
 - r-2. The vehicle storage area shall meet the applicable perimeter landscaping and residential buffer standards of s. 295-405-1.

295-603-2-s Zoning

- s. Light Manufacturing. s-1. The gross floor area devoted to the use shall not exceed 3,600 square feet.
- s-2. The use shall not operate between the hours of 9 p.m. and 7 a.m.
- s-3. The use shall not generate noise or odors in violation of ch. 80.
- s-4. All manufacturing activities shall occur within an enclosed building.
- t. Contractor's Shop. All of the contractor's activities, including those activities that are accessory to the principal use, shall be conducted entirely within a building.
- u. Transmission Tower. u-1. The tower shall comply with the applicable provisions of s. 295-413.
- u-2. The tower does not exceed the district height limit or the tower is accessory to an elementary or secondary school and does not exceed 2 times the district height limit or 150 feet, whichever is less, and is set back from all property lines a distance at least equal to the height of the tower. Any other tower which does not exceed 2 times the district height limit or 150 feet, whichever is less, may be allowed as a special use. All other towers are prohibited.
- v. Substation/Distribution Equipment, Outdoor. v-1. All structures associated with the use shall be screened with type "G" landscaping, as described in s. 295-405.
- v-2. No structure associated with the use shall be located within 25 feet of a street lot line.
- w. Seasonal Market. w-1. The activity shall be located on property owned or leased by the operator of the seasonal market. Alternatively, the market operator may furnish the department with written evidence that the property owner has given the operator permission to use the premises for a seasonal market.
- w-2. If flowers, plants, Wisconsin-grown farm products or Christmas trees constitute at least 75% of the merchandise offered for sale, the activity shall be limited to not more than 90 days in one calendar year. Otherwise, the duration of the seasonal market shall be limited to not more than 14 days in one calendar year.
- w-3. The activity shall not produce glare, spill light or noise in violation of the provisions of ch. 80.
- w-4. Signage shall be limited to not more than 2 signs and a total display area of 16 square feet for all signs combined.
- w-5. Sales shall not occur between the hours of 9 p.m. and 7 a.m.
- w-6. The site shall be restored to its previous condition following termination of the market operation.
- x. Temporary Real Estate Sales Office. x-1. The sales office and any associated model homes or units shall be open only until the homes or units specifically being marketed are sold out.
- x-2. Signage shall comply with the requirements of s. 295-407 and the sign regulations of subch. 5.
- x-3. Customer-accessible restrooms shall be provided.
- x-4. An occupancy permit shall not be required for a temporary real estate sales office meeting the requirements of this paragraph.
- y. Temporary Concrete/Batch Plant. y-1. The plant shall be located on the property it serves or adjacent to the roadway if it is serving a roadway project. Construction projects at other locations shall not be served by the facility.
- y-2. The plant shall be located on property owned or leased by the operator of the plant. Alternatively the plant operator may furnish the department with written evidence that the property owner has given the operator permission to use the premises for a concrete/batch plant. If the operation utilizes the public right-of-way, the operator shall obtain appropriate permissions and permits from the commissioner of public works.
- y-3. No dust from the operation shall blow onto adjacent properties or public right-of-way. The operator shall also provide for the daily removal of material tracked onto the public roadway by equipment coming to or going from the facility.
- y-4. The plant shall not operate between the hours of 9 p.m. and 7 a.m.
- y-5. The plant may operate for a period not to exceed 9 months. When the construction project the plant is serving is complete, the site shall be cleaned and returned to its original condition or improved condition, as appropriate.

y-6. The plant shall be screened with a 9-foot opaque fence, including but not limited to a chain-link fence with inserted slats.

z. Live Entertainment Special Event. z-1. If the event is to occur on the public right-of-way or other public property, the person, firm or organization coordinating the event shall obtain a special event permit in accordance with s. 105-55.5.

z-2. The person, firm or organization coordinating the event shall obtain a festival permit, if required to do so by s. 261-103.

z-3. If the event will include carnival rides, the property owner or carnival operator shall obtain a carnival site permit in accordance with s. 87-14.

z-4. The event shall be located on property owned or leased by the person, firm or organization that is coordinating it. Alternatively, such person, firm or organization may furnish the department with written evidence that the property owner has given the operator permission to use the premises for a live entertainment special event.

3. ACCESSORY USES. a. General. An accessory use to a principal use shall be allowed if it complies with all applicable development standards, all other regulations of this chapter and all provisions of this code relating to odors, smoke, dust or noise, or the open storage of materials or equipment.

b. Motor Vehicle Repair, Service or Maintenance on Lots Used for Residential Purposes. No motor vehicle repair, service or maintenance shall be permitted on any lot used wholly or in part for residential purposes without a certificate of occupancy for such motor vehicle uses, unless the following conditions are met:

b-1. The motor vehicle repaired, serviced or maintained is owned by a person who resides on the lot.

b-2. Not more than one motor vehicle shall be repaired, serviced or maintained at any one time.

b-3. The removal of any vehicle components, including but not limited to engines, transmissions, radiators, wheel assemblies, doors and hoods, shall be performed only within an enclosed garage and out of view of the general public. All vehicle parts, components and repair tools shall be stored within an enclosed garage and kept out of view of the general public. Junk yards shall not be permitted.

b-4. Motor vehicle body work and painting shall be permitted only if a certificate of occupancy for a light motor vehicle body shop has been issued by the department.

c. Home Occupations. Home occupations, except live-work units as defined in s. 295-201, shall comply with the following standards:

c-1. The home occupation shall be subordinate to the residential use of the dwelling unit.

c-2. No one other than a resident of the dwelling unit shall be employed in the conduct of the home occupation.

c-3. No accessory building or open space may be used for the conduct of a home occupation or for the storage of related equipment or supplies. However, up to 50% of private residential garage space may be used for storage of related equipment or supplies provided any parking requirements established by this chapter are met.

c-4. There shall be no external alteration of the dwelling unit and the existence of the home occupation shall not be apparent beyond the boundaries of the site.

c-5. Not more than 20% of the total usable floor area of the principal building and the basement may be devoted to the home occupation.

c-6. The home occupation shall create no additional traffic and require no additional parking above that normally associated with a dwelling unit.

c-7. No signs relating to the home occupation shall be permitted.

d. Rummage Sales. Not more than 2 rummage sales shall occur on a residential premises in one calendar year. No rummage sale shall exceed 3 days in length. Items offered for sale shall be limited to household items from one dwelling unit.

e. Accessory Parking. The location of accessory off-street parking spaces, including parking for 4 or fewer vehicles, shall comply with all applicable parking location standards set forth in s. 295-603-2.

295-605 Zoning

295-605. Design Standards. 1. INTRODUCTION. The purposes of the design standards of this section are to:

a. Maintain Compatibility with Neighborhood Context. An objective of these design standards is to ensure that buildings in commercial districts fit within the context in which they are built. Lot sizes, lot coverage, height and other design parameters vary by district to ensure that the requirements of this section closely match the existing built environment.

b. Allow Flexibility in Development. Flexibility in meeting design standards is achieved by providing ranges, exceptions and alternatives which are consistent with the spirit and intent of this chapter. These ranges, exceptions and alternatives allow various site-specific and project-specific issues to be addressed while still taking into account the intention of the zoning district.

c. Consistency with the Principles of Urban Design. These design standards strive to promote development that is consistent with the "Principles of Urban Design" adopted by the city plan commission as part of the city's comprehensive plan and on file in the office of the commission and in the legislative reference bureau. Commercial development and alterations should not only be compatible with the character of the neighborhood, but also create pedestrian-friendly environments, allow varying degrees of land use diversity within each zoning district, and promote environments which support transportation diversity consistent with neighborhood context.

2. PRINCIPAL BUILDING STANDARDS. a. Introduction. Principal building standards are established to ensure that new construction in commercial districts, as well as additions and alterations to existing buildings, is appropriate for the surrounding context in terms of size, placement, height and design characteristics. The design standards for non-residential and multi-family buildings are set forth in table 295-605-2. When a building contains both residential and non-residential uses, the design standards for non-residential buildings shall apply. Single-family and 2-family dwellings shall meet the design standards of subch. 5, as cross-referenced in table 295-605-2. The provisions of this subsection explain, qualify or specify exceptions to the standards in the table.

b. Street Orientation. b-1. Introduction. Both building placement standards and pedestrian engagement standards, such as but not limited to entrance placement standards and window requirements, relate to a building's relationship to the street and insure that a new building or addition maintains existing contextual relationships. These standards are based on a street ranking system derived from the "Functional Classification of Streets and Highways Map" maintained by the commissioner of public works, which is also presented as the single-line street map found on the city's geographic information system. Under this system, streets are ranked as principal arterial, minor arterial, collector and local streets, in that order. For purposes of this chapter, freeways and the Lake Parkway are not included in this street classification system.

b-2. Primary Street. The highest-ranked street abutting a lot shall be considered the primary street, and its street lot line considered the front of the lot. When a lot is bounded by 2 streets of equal rank, the permit applicant shall specify which street is the primary street.

b-3. Secondary Street. On a lot with 2 or more abutting streets, the second-highest-ranked street, or the other highest-ranking street after the street identified as the primary street pursuant to subd. 2, shall be considered the secondary street, and its street lot line considered the side street. A through lot shall not be required to meet side street setback requirements.

b-4. Other Streets. Each lot with 2 or more street frontages shall have one primary street and one secondary street. The setback requirements of table 295-605-2 shall not apply to any street lot line that does not abut a primary or secondary street.

c. Front Setback Standards. c-1. Intent. Front setback standards are intended to ensure that the front façade or elements of new construction or additions maintain relationships to the primary street that are similar to the corresponding relationships for buildings of similar use in the immediate vicinity. At least 70% of the front façade of a principal building, measured in terms of lineal feet of building frontage, shall meet both the minimum and maximum front setback requirements. The remaining 30% or less of the front façade may be set back any distance from the front street property line.

Table 295-605-2 PRINCIPAL BUILDING DESIGN STANDARDS							
<i>Design Standards for Non-residential and Multi-family Principal Buildings</i>							
	NS1	NS2	LB1	LB2	RB1	RB2	CS
Primary Street							
Front setback, minimum (ft.) (see s. 295-505-2-b)	average	none	average	none	average	none	none
Front setback, maximum (ft.) (see s. 295-505-2-b)	50	average	70	average	none	70	average
Secondary Street							
Side street setback, min. (ft.)	none	none	none	none	none	none	none
Side street setback max. (ft.)	15	5	25	5	none	70	5
Rear street setback, minimum (ft.)	none	none	none	none	none	none	none
Rear street setback, maximum (ft.)	none	none	none	none	none	none	none
Side setback, minimum (ft.)	none	none	none	none	none	none	none
Side setback, maximum (ft.)	none	none	none	none	none	none	none
Rear setback, minimum (ft.)	none	none	none	none	none	none	none
Rear setback, maximum (ft.)	none	none	none	none	none	none	none
Lot area per dwelling unit, minimum (sq. ft.)	2,400	1,200	1,200	800	1,200	800	1,200
Height, minimum (ft.)	none	18	none	18	none	24	none
Height, maximum (ft.)	45	60	45	60	85	85	60
Minimum glazed area, primary street frontage	40%	60%	30%	60%	20%	30%	10%
Minimum glazed area, secondary street frontage	10%	15%	10%	15%	10%	15%	5%
Multiple principal buildings permitted?	yes	yes	yes	yes	yes	yes	yes
<i>Design Standards for Single-family and Two-family Dwellings</i>							
	NS1	NS2	LB1	LB2	RB1	RB2	CS
Refer to design standards in subch. 5 for this residential district	RM1	RM4	RM2	RM5	RM2	RM5	RM4

295-605-2-c-2 Zoning

c-2. Setback Averaging. When setback averaging is required, the average setback shall be determined using the formula described in s. 295-505-2-b-4.

c-3. Building Placement. c-3-a. New Buildings. At least 70% of the front façade of any newly constructed principal building shall be located within the range of the minimum and maximum front setbacks established by table 295-605-2. The remaining 30% or less of the front façade may be set back farther from the front lot line than the maximum front setback, but shall not be located closer to the front lot line than the minimum front setback.

c-3-b. Additions and Alterations. Where portions of an existing building are closer to the front lot line than are the front facades of the nearest adjacent buildings, a new addition or alteration may be placed as close to the front lot line as the portion of the building closest to the front lot line. Where an existing building is set back farther from the front lot line than are the nearest adjacent buildings, an addition or alteration may extend as close to the front lot line as the minimum front setback.

c-3-c. Removal of Portion of Building. No building may be altered by removing a portion of the building such that the front façade of the building will no longer be within the required setback range, or will be even farther from the required range than it already is.

c-3-d. Exception for Motor Vehicle Uses. Where a principal use of a property is a motor vehicle-related use, there shall be no front setback requirements unless stipulated by the board.

c-3-e. Exception for Maximum Setbacks. Notwithstanding any other provision of this subchapter, when averaging is used to determine the maximum front setback, a maximum setback of 2 feet shall always be permitted.

d. Side Street Setback Standards. d-1. Intent. Side street setback standards are intended to ensure that the façade or other elements of new construction or additions maintain relationships to the secondary street in a manner similar to the corresponding setbacks for buildings of similar use in the immediate vicinity.

d-2. Building Placement. d-2-a. New Buildings. At least 70% of the side street façade of any newly constructed principal building shall be located within the range of the minimum and maximum side street setbacks established by table 295-605-2. The remaining 30% or less of the side street façade may be set back farther from the side street lot line than the maximum side street setback, but shall not be located closer to the side street lot line than the minimum side street setback.

d-2-b. Exception for Motor Vehicle Uses. Where a principal use of a property is a motor vehicle-related use, there shall be no side street setback requirements unless stipulated by the board.

e. Intrusions Into Public Right-of-way. See ch. 245 for regulations pertaining to intrusions of structures into the public right-of-way.

f. Building Height. f-1. Exceptions to Height Limitations. All structures shall comply with the height limitations established in each zoning district, except the following:

f-1-a. Chimneys and flues.

f-1-b. Water towers or tanks other than those located on the roof of a building.

f-1-c. Bulkheads, elevator enclosures, penthouses, skylights or water tanks occupying in the aggregate less than 25% of the area of the roof on which they are located.

f-1-d. Parapet walls or cornices extending above the height limit not more than 5 feet.

f-1-e. Monuments, television reception antennae, radio reception antennae, flag poles, spires, church roofs, domes, cupolas or belfries for ornamental purposes and not used for human occupancy.

f-1-f. Churches, convents, schools, dormitories, colleges, libraries and museums in zoning districts which limit height to 45 or 60 feet. Such a building or portion thereof may exceed the height limit of the district if the building, or portion of the building in excess of the limit, is setback from side lot lines a distance equal to one-half the height of the building or portion thereof.

f-1-g. Transmission towers which are in compliance with the height-related standards of s. 295-603-2-u.

f-1-h. Airports. In any area within the city where the height limitations of the Milwaukee county airport approach height ordinances are applicable, such height limitations shall apply, except where the height limitations of this chapter are more restrictive. Exceptions permitted under s. 200-44 and objects of natural growth shall not exceed the height limitations established by the Milwaukee county general ordinances and by s. 114.136, Wis. Stats.

f-2. Exception to Minimum Height Requirement. Motor vehicle-related uses shall not be subject to a minimum building height requirement.

g. Lot Coverage. g-1. General. The lot coverage standards set forth in table 295-605-2 refer to the proportion of a lot occupied by principal buildings. Accessory structures shall not be included when determining principal building lot coverage.

g-2. Exceptions. Motor vehicle uses and fast-food/carry-out restaurants shall not be subject to lot coverage requirements.

h. Conversion of Non-Residential Buildings to Residential Use. A non-residential building may be converted to residential use. The density regulations of table 295-605-2 shall be applicable to any such conversion. Where the conversion would otherwise be prohibited by these density regulations, each existing non-residential unit may be converted to one residential unit. Notwithstanding any other provision of this chapter, any building converted from non-residential use to residential use shall meet the glazing standard specified in table 295-605-2.

i. Design Features. i-1. Intent. The standards of this paragraph are intended to encourage pedestrian-oriented commercial development.

i-2. Entrance Door Orientation. Every new building shall have a primary entrance door on the front façade. A primary entrance door shall not be required on the front façade if there is a primary entrance door on a side façade and that door is within 20 feet of the front façade.

i-3. Glazing. i-3-a. General. All new principal buildings and additions shall have transparent glass windows on both the primary and secondary street frontages according to the percentages listed in table 295-605-2. In addition, no existing building may be altered in such a way that the amount of glazing is reduced below the amount required herein. Whenever a substantial improvement occurs, the building shall meet the glazing requirements of table 295-605-2 at the time the substantial improvement is completed. Non-glass materials such as transparent plastic may not be used to meet transparency requirements.

i-3-b. Area of Required Glazing. The percentage of lineal frontage of the first floor indicated in table 295-605-2 shall have windows at least 4 feet in height with sills not more than 3 feet 6 inches above the interior floor level.

i-3-c. Transparent Glass. Glass in windows or doors used to meet the glazing requirement shall transmit at least 65% of visible daylight (visible transmittance $\geq .65$), regardless of whether the glass is tinted integrally or with applied film. Spectrally selective low-e coatings can meet this requirement.

i-3-d. Interior Spaces. Interior walls parallel to required glazing shall be not less than 6 feet from the plane of the glazing.

i-3-e. Window Coverings. Operable interior window coverings may be used. Such coverings include, but are not limited to, blinds and draperies. No window covering may be permanently affixed or adhered to the window such that the window becomes permanently opaque.

i-3-f. Display Racks and Fixtures. Display racks within 4 feet of a window shall be open-backed and shall not obscure more than 50% of the glazing area.

i-3-g. Structural Elements. Structural elements of a glazing system that are less than 6 inches in width shall be counted as part of the clear glazing.

i-3-h. Sill Height Exception. In NS1, LB1, RS1 and CS districts, the maximum sill height may be raised to not more than 4 feet 6 inches above the finished floor level.

i-3-i. Rear Street Exception. When a rear street frontage is determined to be a secondary street frontage and the building façade facing that street frontage is more than 25 feet from the rear street property line, there shall be no requirement for glazing.

i-4. Alternatives to Glazing. The following alternative window or wall treatments may be used to meet the glazing requirements of subd. i-3:

295-605-3 Zoning

i-4-a. Other First-floor Windows Outside the Area of Required Glazing. Clerestory windows or low windows that are at least 3 feet in height may be used to meet the requirements of subpar. i-3-b, and shall only be counted at half the rate of regular windows.

i-4-b. Display Cases. Display cases that are located in the area of required glazing and are at least 4 feet in height may be used to meet the requirements of subpar. i-3-b, but shall only be counted at half the rate of regular windows.

i-4-c. Wall Design. On secondary street frontages, walls that are designed to avoid long, flat facades may be used to meet the requirements of subpar. i-3-b, subject to approval by the commissioner. In order to be counted towards the glazing requirement, the entire wall shall be designed in this manner and individual sections of flat, blank wall surface shall not exceed 25 feet in length.

i-4-d. Windows not Meeting Transparency Standards. Windows that do not meet the transparency standards of subpar. i-3-c shall be counted at 25% of the rate of regular windows.

i-4-e. Other Elements. Subject to approval by the commissioner, other elements that are integrated into the façade of a building may be used to meet the requirements of subpar. i-3-b and shall be counted at the same rate as regular windows. Such integrated elements include, but shall not be limited to, bus shelters and automatic teller machines.

i-5. Overhead Garage Doors Facing Streets. For any new building or addition constructed in the NS2, LB2, or RB2 district, an overhead garage door which faces the street shall be set back at least 4 feet from the front façade of the main building mass.

i-6. Metal Building Walls. The use of corrugated metal, a metal panel-and-batten system or any other pre-engineered metal building technology on any front façade or street façade located within 100 feet of a street shall be prohibited for any new building construction, addition, or substantial improvement as of November 20, 2004. This provision shall not preclude the use of metal panels or siding in detailing soffits, fascia, dormers, coping, cupolas and similar architectural features, provided the metal materials cover not more than 15% of the total façade, nor shall it preclude the use of metal building walls on additions to existing buildings constructed of similar materials.

3. ACCESSORY STRUCTURE STANDARDS. a. General Requirements for Accessory Buildings. a - 1 .

The minimum front setback shall not be less than that of the principal building.

a-2. The minimum side street setback shall not be less than that of the principal building.

a-3. No side setback shall be required.

a-4. If access to a garage is provided from an alley, a minimum rear setback of 4 feet shall be required. Otherwise, no rear setback shall be required.

a-5. Maximum building height shall not exceed the district height limit found in table 295-605-2.

a-6. The number of accessory buildings shall not be limited.

b. Structures Accessory to Single-family and Two-family Dwellings. Any structure accessory to a single-family or 2-family dwelling shall meet the requirements set forth in table 295-505-3.

c. Deck Skirting. Skirting to screen the area underneath the deck shall be provided for any deck that is more than 2 feet above grade. Skirting shall not be required if any of the following are true:

c-1. The deck is more than 30 feet from any property line.

c-2. The deck is located within 3 feet of a property line and an opaque fence at least 4 feet high is present or is constructed along that property line such that the view of the deck from the neighboring property or public way is obscured.

c-3. The area adjacent to the deck is landscaped with plantings that obscure the view of the underside of the deck from the neighboring property or public way.

d. Mechanical Equipment. Mechanical equipment such as, but not limited to, air-conditioning condensers and utility boxes shall be permitted in portions of side yards and rear yards outside required setback areas.

4. SITE STANDARDS
 - a. Applicability. Unless otherwise noted, the provisions of this subsection apply to all residential and non-residential uses.
 - b. Parking Spaces.
 - b-1. General. Off-street parking spaces for uses in commercial zoning districts shall be provided in accordance with the requirements of s. 295-403-2 and shall meet the design standards of s. 295-403-3.
 - b-2. Reduction Prohibited. The number of parking spaces provided for a use in a commercial zoning district shall not be reduced below the number required by s. 295-403-2.
 - b-3. Location of Parking Spaces. The location of parking spaces shall be in accordance with table 295-603-1 and any corresponding limited use standards.
 - b-4. Maximum Number of Vehicles. Not more than 4 motor vehicles may be parked outdoors on a lot containing a single-family or 2-family dwelling.
 - b-5. Unregistered Vehicles. No motor vehicle lacking valid license plates shall be parked for a period exceeding 30 days outside any structure or lot used in whole or in part for residential purposes.
 - c. Access Drives.
 - c-1. Configuration. An access drive shall generally traverse the front setback at a right angle. The commissioner of public works shall approve the location and design of the curb cut and driveway apron for the access drive.
 - c-2. Width. An access drive shall not exceed 30 feet in width.
 - d. Pedestrian Access.
 - d-1. General. Where a lot is adjacent to a public sidewalk, each principal building on the lot shall be served by a clearly identifiable walkway leading from the public sidewalk to the entrance to the building. The presence of an access drive does not fulfill this requirement.
 - d-2. Paving. All required pedestrian access ways shall be paved with non-asphalt materials.
 - d-3. Width. All required pedestrian access ways shall be at least 5 feet in width.
 - e. Landscaping.
 - e-1. Intent. Landscaping shall be designed as an integral part of any development in a commercial zoning district. As in residential and industrial zoning districts, parking lots, dumpsters and similar site features shall be screened such that they are not visible from public streets and neighboring residential properties.
 - e-2. Parking Lots. All uses, with the exception of single-family and 2-family dwellings, shall provide parking lot landscaping in accordance with s. 295-405.
 - e-3. Dumpsters. A dumpster storage area for a non-residential building constructed after October 1, 2002, of a residential building containing more than 4 dwelling units and constructed after October 1, 2002, shall be screened with type "G" landscaping, as described in s. 295-405, or shall be incorporated into the structure it serves.
 - f. Loading Docks. Where loading for more than 2 truck bays is in a yard facing and visible from a public street or a non-industrial district, the loading docks shall be screened with type "G" landscaping, as described in s. 295-405. These standards may be waived in whole or in part, or compliance with them may be delayed, if visibility of the loading docks is limited by changes of grade, natural features, elevated roadways, existing buildings or similar obstructions.
 - g. Fences.
 - g-1. General. Fences shall be permitted anywhere on a lot in a commercial zoning district, including placement along property lines. For the purposes of this paragraph, the term "fence" shall include a wall or other similar structure.
 - g-2. Fences along Streets. Fences along streets shall not exceed a height of 4 feet, with the following exceptions:
 - g-2-a. A fence may be erected to a height of 6 feet if it is set back at least 5 feet from the sidewalk, or 5 feet from the property line if there is no sidewalk. In no case does this provision allow a fence to be erected in the public right-of-way, unless a special privilege allowing such fence has been granted by the common council pursuant to ch. 245.
 - g-2-b. An ornamental metal fence may be erected to a height of 8 feet. Such fence may include masonry piers, provided the fence is at least 50% open overall. An ornamental metal fence may also be constructed atop a masonry wall, provided the combined height of the wall and fence does not exceed 8 feet and the portion of the wall/fence structure above 6 feet high is at least 50% open.

295-605-5 Zoning

g-3. Fences along Side and Rear Lot Lines. A fence located along a side lot line or a rear lot line shall not exceed a height of 8 feet.

g-4. Orientation of Supporting Members. The vertical and horizontal supporting members of a fence shall face the interior of the lot on which the fence is located.

g-5. Fence Gates and Trellises. At a gate, walkway or other entrance area, a decorative gate or trellis may extend above the permitted fence height to a maximum of 10 feet in height. A decorative gate or trellis shall not exceed 6 feet in width.

g-6. Public-Right-of-Way. A fence or retaining wall may extend into the public right-of-way to the extent allowed by, and only in accordance with, a special privilege granted by the common council pursuant to s. 245-12.

g-7. Fences at Construction Sites. Notwithstanding any other provisions of this paragraph, fences not exceeding 9 feet in height may be erected around construction sites and shall be removed immediately upon completion of the project.

g-8. Fences at Sports Facilities. Notwithstanding any other provision of this paragraph, the commissioner may permit a fence in excess of 6 feet in height in specific locations on a premises to prevent balls and other objects from damaging adjoining buildings or premises.

g-9. Fences as Part of Required Screening. Notwithstanding any other provisions of this paragraph, a fence may be erected to the height necessary to comply with the screening requirement of s. 295-405-3.

g-10. Prohibited Fence Materials. Barbed-wire, concertina-wire and razor-wire fences are prohibited.

h. Vision Triangles. A fence or other opaque or semi-opaque object located near the intersection of a street with an alley, access drive or another street shall be in compliance with the vision triangle regulations of s. 295-405-3.

i. Lighting. The regulations for lighting in commercial zoning districts are set forth in s. 295-409.

5. SIGNS. a. General. The design standards for signs in commercial districts are set forth in table 295-605-5. As described in s. 295-407, signs are divided into 2 categories, type "A" and type "B". General standards for each of these categories are found in s. 295-407. The provisions of this subsection explain, qualify or specify exceptions to the standard in table 295-605-5, which pertain specifically to type "A" and type "B" signs in commercial zoning districts.

b. Sign Limitation Based on Lineal Footage. Where table 295-605-5 links the maximum number or area of signs to lineal footage, the lineal footage referred to is the length of the building facade. In each 25-foot segment, the square footage of all signs shall not exceed the maximum area specified in the table and the size of a sign in a facade segment less than 25 feet may be determined by prorating. The square footage allocation for 2 adjoining facade segments may be combined to allow one sign larger than the maximum amount specified. Only one wall, projecting or canopy/hood sign may be located in each facade segment.

c. Bonus Provision for Type "B" Freestanding Signs. If a monument-type base meeting the base standard for a type "A" freestanding sign is provided and the sign does not exceed 8 feet in height, the maximum display area shall be 10 square feet more than the maximum display area specified in table 295-605-5.

d. Standards for Multiple Freestanding Signs. Where more than one freestanding sign is permitted on a site, these signs shall comply with the following standards:

d-1. No 2 freestanding signs may have display areas that are oriented to the same street.

d-2. The signs shall be located as far apart as is possibly practicable or be separated by a building.

e. Combination Type A and B Signs. Signs that contain elements of both type A and type B signs shall be permitted as long as the size of each element does not exceed its prorated share of total display area, in accordance with s. 295-205-5-d.

f. Signs Limited by Site. For purposes of applying sign regulations only, a site may include a parcel described by a lease, provided the lease is at least 20 years in length.

Zoning 295-605-5-g

g. Temporary Signs. The following temporary signs shall be permitted in all commercial zoning districts:

g-1. A sign pertaining to the construction of a building or the sale or lease of vacant land shall not exceed:

Zoning District	Max. Sign Area
NS1 and NS2	36 sq. ft.
LB1, LB2 and CS	48 sq. ft.
RB1 and RB2	72 sq. ft.

g-2. A sign not exceeding 36 square feet erected and maintained on a lot to advertise the leasing, rental or sale of a building or other improved real estate.

295-605-5 Zoning

<p align="center">Table 295-605-5 COMMERCIAL DISTRICT SIGN STANDARDS</p>							
	Zoning District						
	NS1	NS2	LB1	LB2	RB1	RB2	CS
<i>Freestanding Signs</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>
Maximum number	1 per site	1 per site	1 per street frontage	1 per site*	1 per street frontage	1 per street frontage	1 per site
Type "A" max display area (sq. ft.)	60	40	100	60	150	100	60
Type "B" max. display area (sq. ft.)	32	20	50	32	75	50	32
Maximum height	10	6	14	14	20	20	14
<i>Wall Signs</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>
Maximum Number	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.
Type "A" max display area (sq. ft.)	40	40	60	40	60	60	40
Type "B" max. display area (sq. ft.)	25	25	32	25	32	32	25
<i>Projecting Signs</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>	<i>permitted</i>
Maximum number	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.
Type "A" max display area (sq. ft.)	50	50	60	50	100	60	50
Type "B" max. display area (sq. ft.)	25	25	30	25	50	30	25
<i>Awning Signs</i>	<i>type "A" permitted only</i>	<i>type "A" permitted only</i>	<i>type "A" permitted only</i>	<i>type "A" permitted only</i>	<i>type "A" permitted only</i>	<i>type "A" permitted only</i>	<i>type "A" permitted only</i>
Maximum number	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.
Type "A" max display area (sq. ft.)	20	10	20	10	20	10	20

Table 295-605-5 COMMERCIAL DISTRICT SIGN STANDARDS							
	Zoning District						
	NS1	NS2	LB1	LB2	RB1	RB2	CS
Canopy and Hood Signs	permitted	permitted	permitted	permitted	permitted	permitted	permitted
Maximum number	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.	1 per 25 lineal ft.
Type “A” max display area (sq. ft.)	50	50	60	50	100	60	50
Type “B” max. display area (sq. ft.)	25	25	30	25	50	30	25
Roof Signs	not permitted	not permitted	permitted	type “A” permitted only	permitted	permitted	type “A” permitted only
Maximum number	NA	NA	1 per building	1 per building	1 per building	1 per building	1 per building
Type “A” max display area (sq. ft.)	NA	NA	100	100	100	100	50
Type “B” max. display area (sq. ft.)	NA	NA	32	0	32	32	0
Off-premise Signs	not permitted	not permitted	permitted	permitted	permitted	permitted	permitted
Maximum number	NA	NA	1 per site	1 per site	1 per site	1 per site	1 per site
Maximum display area per sign (sq. ft.)	NA	NA	300	300	300	300	300
Minimum distance between signs	NA	NA	500ft. between any 2 ground or roof signs; 200ft. between a ground or roof sign and a wall sign; 200 ft. between any 2 wall signs				
Maximum height, freestanding sign (ft.)	NA	NA	35	35	35	35	35
Maximum height, wall sign (ft.)	NA	NA	40	40	40	40	40
Maximum height, roof sign	NA	NA	25 ft. above roof				
* Except 2 shall be permitted if the site fronts on 3 streets or has continuous street frontage of at least 240 feet.							

[Pages 830-840 are blank]